

CU (CONTROL UNIT) P2010



- ▶ For vacuum pump P2010.
- ▶ CU with electric valves for vacuum on/off and blow-off, alternatively with automatic quick-release.
- ▶ LED indicators for status of valve signal.
- ▶ Quick and easy mounting with push-in connections.

TECHNICAL DATA

Description	Unit	Value
Feed pressure, max.	MPa	0.7
Material		PA, NBR, Al, SS, POM, CuZn, PE
Temperature range	°C	-5-50
Connection, compressed air	mm	3 x Ø4
Function, on/off		NC
Voltage	VDC	24 (22-28)
Response time	ms	8-10
Current consumption	mA	60
Ripple, max.	V _{rms}	1
Display		LED indicator
Flow @ P ₁ =6 bar and Δp=1 bar	NI/s	0,25
Electric connection		2-pin

TECHNICAL DATA, SPECIFIC

Description	Unit	Value		
		0110349	0110352	0110353
Weight	g	63	50	52
Volume, Quick-Release tank	cm ³	NA	0.9	2.3
Flow, blow-off @ P ₁ =6 bar and Δp=1 bar	NI/s	0,25	NA	NA
Dimension, WxDxH	mm	44x10x51,2	44x10x51,9	44x10x79,9

ORDERING INFORMATION

Description	Art. No.	ECW	ACW
CU P2010	0110349	v	
Quick-Release 0 electric, P2010	0110352	v	
Quick-Release 3 electric, P2010	0110353	v	v

ORDERING INFORMATION, ACCESSORIES

Description	Art. No.	ECW	ACW
Cable 2-pin female, L=2m	0110157	v	
Plug M8x1	0110155		
Quick-Release tank P2010	0110156		

v = Available in European Central Warehouse (ECW)/Asian Central Warehouse (ACW).