

## CU (CONTROL UNIT) P3010, P5010 & P6010



- ▶ For vacuum pumps P3010, P5010 and P6010.
- ▶ CU with electric valves for vacuum on/off and blow-off.
- ▶ Mechanical valve for blow-off flow adjustment.
- ▶ Special M12 4-pin cable assembly with LED for status of valve signal.

### TECHNICAL DATA

Description	Unit	Value
Feed pressure, max.	MPa	0.7
Material		PA, NBR, Al, SS, PMMA
Temperature range	°C	0–50
Function, on/off		NC
Voltage	VDC	24 (22–28)
Safety classification		IP65 [NEMA 4]
Humidity	%RH	90
Current consumption	mA	60
Ripple, max.	V <sub>rms</sub>	1
Electric connection		M 12 4-pin

For dimensions, please go to data sheet for vacuum pumps P3010, P5010 and P6010.

### TECHNICAL DATA, SPECIFIC

Description	Unit	Value		
		P3010	P5010	P6010
Flow, blow-off @ P <sub>1</sub> =6 bar and Δp=0.5 bar	l/s	0–7.5	0–7.5	0–7.5

### ORDERING INFORMATION

Description
Available in product configuration, please go to data sheet for vacuum pumps P3010, P5010 and P6010.

### ORDERING INFORMATION, ACCESSORIES

Description	Art. No.	ECW	ACW
Cable M12 4-pin female, LED indicator, PUR, L=5m	0118013	v	

v = Available in European Central Warehouse (ECW)/Asian Central Warehouse (ACW).